



An excellent general harvester head for thinning, selective cutting and small regeneration felling.

The large opening of the delimbing knives and the five-row tracks ease the production and harvesting of fuelwood.

The rear knive and rigid saw housing ensure successful felling. Even larger trunks remain securely in the harvester head, and the positioning for sawing is accurate in a Keto-typical manner.

The strong two-cylinder tilt allows the handling of even larger trees in an upright position. The fully rotating rotator revolutionises the usability of the harvester head. With patented hydraulics output and return, as well as electricity passthrough.

Technical data

Height in felling position

| Height in felling position | 1305 mm |
|-------------------------------|------------------------|
| Height in processing position | 1950 mm (with rotator) |
| Width in open position | 1320 mm |
| Width in closed position | 1020 mm |
| Length in processing position | 1305 mm |
| Depth in felling position | 1220 mm |
| Weight | 820 kg (with rotator) |
| Felling diameter | 470 mm |
| Delimbing diameter | 400 mm |
| Delimbing knives | 4 |
| Maximum working pressure | 250 bar |
| Recommended pump capacity | 190 l/min |
| Saw bar length | 22" |
| Feeder type | 5-line track |
| Feed force | 21 kN |
| Maximum tree weight | 1300 kg |
| Maximum feed speed | 4,9 m/s |
| Engine power of base machine | 90 kW |
| | |

13∏5 mm



Jarmo JukarainenTel. +358 40 132 1845
jarmo.jukarainen@kone-ketonen.fi

SALES/OVERSEAS

Jari Hakala Tel.+358 20 734 4651 jari.hakala@kone-ketonen.fi

